



## RR7-II Atlantic Reclining Bathing System

The RR7-II Atlantic is designed for care facilities looking for a more time efficient and labor-saving bathing solution. The RR7-II Atlantic has a unique tilting function, which allows residents with challenging conditions to recline in a contoured seat and become immersed in warm water. At only 24 gallons to pre-fill the foot well, water usage and the associated costs are greatly reduced.

The sleek exterior design of the RR7-II Atlantic will give your bathing area the look of a luxury spa. Caregivers will enjoy its ease of use and the improved quality of care they can provide the resident. Featuring a full range of standard and optional features, the RR7-II Atlantic is designed to enhance the bathing experience for the resident.

The Rane Bathing Systems product line provides a unique combination of style, ease of use, comfort, and low cost of ownership.

- ◆ **Made in the USA.** Manufactured in Sparta, TN from the highest quality components and materials.
- ◆ **A “Best in Class” Warranty** resulting in low cost of ownership.
- ◆ **Full set of Standard Features**, including an easy-to-use control panel, thermostatic mixing valve, handheld shower wand, built-in disinfection system, analog thermometer, head pillow, and 3/4” stainless steel mesh supply lines.
- ◆ **Nationwide Distribution and Customer Service.**



The RR7-II Atlantic features an easy-to-use control panel, which includes a thermostatic mixing valve, tub-fill valve, shower valve, analog thermometer, and a CleanRane™ Air Spa control pad (if equipped).



**MADE IN THE USA**

## Standard Features

- ◆ **Thermostatic Mixing Valve** with anti-scald protection that dispenses 15 gallons per minute for fast tub fill.
- ◆ **Built-in Disinfection System** that is the most time-efficient solution for disinfection of the bath's external surfaces and minimizes the risk of cross-infection.
- ◆ **Handheld Shower Wand** for hair and upper body washing, which can be used at the same time the tub is filling.
- ◆ **Analog Thermometer** for monitoring tub-fill and shower wand temperatures.
- ◆ **Three Plumbing Configurations** to choose from; side, front, or island configuration. The island configuration allows 360° unobstructed access for the caregiver, and with no visible hook-up hoses or cords.
- ◆ **Head Pillow** with suction cups for comfort and head support.
- ◆ **3/4" Supply Lines** constructed of stainless steel mesh clad.



The sleek design of the RR7-II Atlantic will give your bathing area the look of a luxury spa.

## Optional Features

- ◆ **CleanRane™ Air Spa System** with variable speeds and pulse mode that enhance the therapeutic and relaxing effects of bathing for the resident.
- ◆ **Auto-Fill** is a time-saving feature that enables the caregiver to fill the tub to a pre-set level (24 gallons).
- ◆ **Battery Back-up** in case of power failures.
- ◆ **Digital Scale** for accurate weight reading at bath time.



The built-in disinfection system cabinet is conveniently located on the end of the tub for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.

## Why CleanRane™ Air Spa System?

The CleanRane™ Air Spa System enhances the therapeutic and relaxing effects of bathing and provides a pleasant experience for the resident. Hydromassage provides millions of preheated air bubbles in the water which increases stimulation of peripheral blood circulation, reduces pain and inflammation in the joints, gently massages away dirt, and induces deeper relaxation. The hygienic and low maintenance CleanRane™ Air Spa System features 12 air jets with spring loaded check valves for back flow prevention, which prevents water from entering the air lines. Unlike most other whirlpool and air spa systems, the CleanRane™ Air Spa System does not allow water to enter the air lines, which can become a breeding ground for bacteria and mold. The highly efficient CleanRane™ Air Spa System simplifies disinfection and reduces the possibility of cross-contamination. The motor is quiet, efficient, and has a ceramic heating element that blows warm air to help maintain the water temperature and warm the surface of the tub.



The air jets on the CleanRane™ Air Spa System feature spring loaded check valves for back flow prevention, eliminating the extra step to disinfect the air lines.

## Technical Specifications

|                                    |                                      |                             |                                     |
|------------------------------------|--------------------------------------|-----------------------------|-------------------------------------|
| Width:                             | <b>34"</b>                           | Weight capacity (resident): | <b>450 lbs. / 204.5 kg</b>          |
| Length:                            | <b>73"</b>                           | Water capacity (occupied):  | <b>38 gallons / 143.8 L</b>         |
| Length (reclined):                 | <b>88"</b>                           | Water capacity (foot well): | <b>24 gallons / 90.8 L</b>          |
| Adjustable leveling legs:          | <b>2" maximum</b>                    | Fill time (foot well):      | <b>1 minute, 36 seconds</b>         |
| Height:                            | <b>51"</b> (lowest setting)          | Drain time (foot well):     | <b>2 minutes, 10 seconds</b>        |
| Height (door in upright position): | <b>78"</b> (lowest setting)          | Drain size:                 | <b>1.5"</b>                         |
| Seat width (interior):             | <b>24"</b>                           | Water supply inlet:         | <b>3/4" diameter</b>                |
| Seat height:                       | <b>21"</b> (lowest setting)          | Electrical supply:          | <b>115V AC; 60Hz; 15 amp</b>        |
| Transfer device access:            | <b>5" H X 31" W</b> (lowest setting) | Door configuration:         | <b>Upward swing, Left side only</b> |

**UL/CSA Certifications:** ANSI Z21.20 / UL 1795 | CSA C22.2 No. 218.2 | ANSI Z124.1.2 (2005): CAN / CSA B45

**Warranty:** **5 yrs.** for external finishes and composite shell, **3 yrs.** for all moving and stationary parts, and **lifetime** on the door seal.